PUNCHING-OUT/TAKING-OUT DEVICE FOR TESTPIECE

(11) 6-273292 (A) (43) 30.9.1994 (19) JP

Appl. No. 5-83962 (22) 19.3.1993

NIPPON STEEL CORP(1) (72) HIDETAKA YAMASHITA(2)

(51) Int. Cl⁵. G01N1/04,B21D28/00,B21D28/02

PURPOSE: To automatically take out a testpiece efficiently from a sample mem-

CONSTITUTION: A specifies the taking out enabled region for the testpiece which is to be taken the testpiece from a sample member under the control by an NC controller above-described result, kind of the testpiece, size and the standard coordinates out on the basis of the order specification by the upper rank calculator (Step controlled by an upper rank calculator, and is equipped with a means which which are previously set (Step 103). punching out order of each testpiece by an NC controller on the basis of the 101, 102), and a means which determines the punching out coordinates and the punching out taking out device for a testpiece takes out

28 x 38

90×100 100×100

(5103

52

BEST AVAILABLE COPY

LEGENDE zu den Bibliographiedaten

(54) Titel der Patontanmeldung (11) Nummer der JP-A2 Veröffentlichung

(21) Aktenzeichen der JP-Anmeldung

(52) Japanische Patentklassifikation

(51) Internationale Patentklassifikation

(43) Veröffentlichungstag

(71) Anmelder (22) Anmeldetag in Japan (72) Erfinder





